



SHRINK WRAPPERS



Smipack FP6000CS

Modularity and excellent price/quality ratio are the main features characterizing the fully automatic L-sealers of the FP6000CS.

- Automatic L-sealer.
- Output up to 3,000 packs/hour.
- Sealing bar: 640x510mm.
- Maximum pack height: 200mm.
- Conveyor closing system included.
- Motorized center seal system.
- 20 on memory programs.
- Available on request in stainless steel.

The FP series can handle Polyolefin and Polyethylene centerfolded film and runs up to 3,000 packs/hour.



FP6000CS+T450

FP6000CS can indeed be supplied with or without shrink tunnel. The shrink tunnel and an optional conveyor model adds flexibility and increases productivity.



Shrink Tunnel T450

T450 is a single-chamber shrink tunnel. This shrink tunnel features FLXMOD® control system, allowing a simple and precise control of all the machine operations.



Conveyor Module GH1000/400

GH1000/400 is the basic model conveyor module for FP6000CS+T450 system. The belts of the GH module can be connected directly to the L-sealers and are equipped with a speed regulator which is independent of the packer.



Smipack S560NA

The S560NA is the ideal solution for companies looking for outputs up to 900 packs per hour.

- Sealing and shrinking in one operation.
- Output rate up to 900 packs/hour.
- PTFE-coated sealing blade.
- Air cooling of the machine frame.
- Quick adjustment of the packaging plate height by means of an external crank.
- Hood hold-down electromagnet.
- Automatic hood release.
- Automatic pack discharge by means of a motorized conveyor.
- Film handled: PVC, Polyolefin up to 30 micron.



Smipack SL55

The SL55 of L-sealing hood packers is capable to produce outputs ranging up to 300 packs/hour.

- Sealing and shrinking in one operation.
- Output rate up to 300 packs/hour.
- PTFE-coated sealing blade.
- Height adjustment of the internal packaging plate.
- Mobile product-holding plate, loose from the film reel support to allow a better adjustment of the film to the pack size.
- Hood hold-down electromagnet.
- Automatic hood release.
- Air cooling of the machine frame.
- Film handled: PVC, Polyolefin up to 30 micron.

SPECIFICATIONS

Model	FP6000CS	T450	GH1000/400
Type	Packer	Shrink tunnel	Conveyor module
Power supply	380/415 V, 3PH+N+PE / 220/240 V, 3PH+PE, 50/60 Hz	380/415 V, 3PH+N+PE / 220/240 V, 3PH+PE, 50/60 Hz	220/240 V, 1PH+N+PE, 50/60 Hz
Installed power	3,100 W	8,000 W	370 W
Compressed air pressure	6 bar	-	-
Compressed air consumption	6 NI/pack	-	-
Sealing bar	640x510 mm	-	-
Maximum pack height	200 mm	230 mm	-
Speed of conveyors	10-30 m/min.	2.8-18, 80 m/min.	6-28 m/min.
Output up to	3,000 packs/hour	-	-
Maximum size film reel	600 - ø 350 mm	-	-
Dimensions (WxDxH)	2,180x1,545x1,525-1,655 mm	1,310x835x1,440 mm	1,080x640x895-1.165 mm
Weight	660 kgs	187 kgs	75 kgs

Model	SL55	S560NA
Type	L-seal packer + shrink wrapper	L-seal packer + shrink wrapper
Power supply	220-240 V, 1PH+N+PE, 50/60 Hz	220-240 V, 1PH+N+PE, 50/60 Hz
Installed power	3,700 W	3,740 W
Sealing bar	560x430 mm	560x430 mm
Maximum pack height	260 mm	260 mm
Output up to	300 packs / hour	900 packs / hour
Maximum size of film reel	600 - ø 250 mm	600 - ø 300 mm
Dimensions with supports	1,260x805x1,100 mm	-
Dimensions with stand	1,240x805x1,102 mm	2,010x790x1,115 mm
Machine Net weight / supports / stand	77 / 11 / 18 kgs	156 kgs

Notice:

- Production rates are based on optimal operating conditions and may vary depending on stock and environmental conditions.
- As part of our continuous product improvement program, specifications are subject to change without notice.

NEOSYS VIETLOI COMPANY LIMITED

Showroom: No.26B, Street 10, Thao Dien Ward, Dist.2, HCMC, Vietnam
 HN Branch: 3rd Floor, No.6, Lane 2, Quan Ngua St., Ba Dinh Dist., Hanoi, Vietnam
 Tel: (+8428) 22532772/ 25532773 - Fax: (+8428) 22532771
 Website: www.neosys-vietloi.com.vn
 Email: info@neosys-vietloi.com.vn
Hotline: 0902 886 117

