



EZF-600

Fully automatic, utmost user-friendly model.

- All the setting and operation can be done via the touch screen.
- Features paper feed pressure & separator pressure adjustment.
- Automatic feed table elevation and delivery roller setting.
- An optional device allows the EZF-600 to perforate, score and slit papers instead of folding.
- The most productive, reliable and user-friendly paper folder at its class.



Paper feed pressure adjustment helps the machine to feed wider range of stocks.



Separator pressure adjustment prevents double feeds.

Specifications of EZF series

Model	EZF-600	EZF-500	EZF-200	EZF-100
Folding position setting	Automatic	Automatic	Manual	Manual
Max. Paper size	300 x 432mm			
Min. Paper size	91 x 128mm (Single fold only)			
Speed sheets/hr. (A4 Single fold)	1,800 - 14,400		Standard mode: 2,400/6,000/10,800 Noise reduction mode: 3,600 Thick paper mode: 3,600 Quick mode: 14,400	
Paper Quality	46.5 - 160gsm (Single fold : up to 230gsm) *Depending on paper type		46.5 - 140gsm (Single fold : up to 210gsm) *Depending on paper type	
Paper stacking capacity	500 sheets (64 gsm)			
Operation	Color touch screen (Addition/Subtraction)		Buttons + 4 digit counter (Addition/Subtraction)	
Folding pattern	6 kinds (Single, letter, zigzag, double parallel, fold-out, gate)			
Double feed detection	.	.	-	-
Fold pattern memory	36 kinds	36 kinds	-	-
Fine adjustment memory	36 kinds	36 kinds	-	-
Odd-size paper folding pattern memory	24 kinds	12 kinds	-	-
Cross fold	.	.	.	Optional
Paper jam detection
Error map
Paper feed/separator pressure adjustment	.	-	-	-
Feed table elevation	.	-	-	-
Paper ejection	Belt	Belt	Belt	Natural
Ejection roller setting	Automatic	Manual	Manual	-
Quick release rollers	.	.	.	-
Options	Perforation, scoring, slitter		-	Paper guide for cross folding
Dimensions (W x D x H mm)	1,030x545x500	1,030x545x500	1,010x545x500	800x545x500
Net Weight	30.6kg	29.6kg	26.8kg	25.2kg
Power Consumption	50W (100-240VAC, 50/60Hz)			

*Production rates are based on optimal operating conditions and may vary depending on stock and environmental conditions.

*As part of our continuous product improvement program, specifications are subject to change without notice.

NEOSYS VIETLOI COMPANY LIMITED

Showroom: No.26B, Street 10, Thao Dien Ward, Dist.2, HCMC, Vietnam
 HN Branch: 3rd Floor, No.6, Lane 2, Quan Nguu St., Ba Dinh Dist., Hanoi, Vietnam
 Tel: (+8428) 22532772/ 25532773 - Fax: (+8428) 22532771
 Website: www.neosys-vietloi.com.vn
 Email: info@neosys-vietloi.com.vn
Hotline: 0902 886 117

