



EBA 2331

EBA 5131

EBA 5141

Model	2331 S	2331 C	2331 C	2331 CCC	5131 C	5131 C	5131 CCC	5141 S	5141 C	5141 C	5141 CC	5141 CCC
Feed opening, mm	310	310	310	310	310	310	310	405	405	405	405	405
Shredder type	strip cut	cross cut	cross cut	fine cut	cross cut	cross cut	fine cut	strip cut	cross cut	cross cut	fine cut	fine cut
Shred width, mm	4	4 x 40	2 x 15	0.8 x 5	4 x 40	2 x 15	0.8 x 5	6	4 x 40	2 x 15	0.8 x 12	0.8 x 5
Performance in sheets, A4 paper 70 g/m <sup>2</sup>	30-32	25-27	15-17	5-7	40-45	25-30	11-12	50-55	40-45	25-30	15-17	10-11
Performance in sheets, A4 paper 80 g/m <sup>2</sup>	26-28	21-23	13-15	4-6	34-39	21-26	9-10	42-47	34-39	21-26	13-15	8-9
Security ISO / IEC 21964 (DIN 66399)	P-2	P-4	P-5	P-7	P-4	P-5	P-7	P-2	P-4	P-5	P-6	P-7
Shreds also				-	  		-	  	  		-	-
Paper clip proof solid steel cutting shafts	•	•	•	-	•	•	-	•	•	•	-	-
Cutting shaft warranty for 10 years	•	•	•	-	•	•	-	•	•	•	-	-
Automatic oiler	-	optional	optional	optional	standard			standard				
Shred speed, m/sec.	0.08	0.10	0.10	0.09	0.15	0.15	0.15	0.19	0.15	0.15	0.15	0.18
Volume of cabinet in litres	140				180			210				
Shred bin volume in litres	120				140			165				
Power connection, volts / Hz (single phase) <sup>1</sup>	230 / 50 / 1~				230 / 50 / 1~			230 / 50 / 1~				
Motor capacity, W	640				1600			1600				
Automatic start/stop via photo cell	•				•			•				
ECC – Electronic Capacity Control	•				•			•				
Control element	EASY-SWITCH				EASY-SWITCH			EASY-SWITCH				
SPS Safety Protection System:	•				•			•				
– Patented safety flap in the feed opening	electronic				electronic			electronic				
– Automatic reverse / automatic power cut-off	•				•			•				
– Automatic cut-off if shred bin is full	•				•			•				
– Electronic door protection	•				•			•				
– Double motor protection	•				•			•				
– Zero energy standby mode	•				•			•				
Awarded the "Blue Angel" <sup>2</sup>	•				•			•				
High quality wooden cabinet, mobile on castors	•				•			•				
Dimensions, mm (H x W x D)	930 x 538 x 470				1020 x 548 x 590			1010 x 640 x 590				
Weight, kg	52				102			115				

## NEOSYS VIETLOI COMPANY LIMITED

Showroom: No.26B, Street 10, Thao Dien Ward, Dist.2, HCMC, Vietnam  
 HN Branch: 3rd Floor, No.6, Lane 2, Quan Ngua St., Ba Dinh Dist., Hanoi, Vietnam  
 Tel: (+8428) 22532772/ 25532773 - Fax: (+8428) 22532771  
 Website: www.neosys-vietloi.com.vn  
 Email: info@neosys-vietloi.com.vn

Hotline: 0902 886 117

<sup>1</sup> other voltages available

<sup>2</sup> for high energy efficiency

