

Floor type paper drills (Spindle-stroke type)

Heavy duty drill with programed pitch bar

High rotation speed spindle up to 2,200 rpm with incredibly accurate drill bits, and newly deveoped controller and inverter makes perfectly sharp edge holes on every paper.

Easy drill bit exchange and depth setting / adjustment.

Waste chute keeps the table clean and keeps the machine accurate.



XA-2

Specifications

Model	XA-2, XA-2W, XA-4, XA-4W
Type	Floor type
Drilling system	Auto spindle stroke
Number of head	2(Up to 4 with XA-4, XA-4W)
Head distance	38 - 310mm / 1.45" - 12.2" (38 - 400mm / 1.45" - 15.8" with 2W, 4W)
Operation	Foot switch
Stroke speed	Freely adjustable
Spindle rotating speed	Freely adjustable(Option)
Drill bit height adjustment	Independently by standrad tool (25mm)
Maximum drilling thickness	50mm (Up to 60mm with optional kit)
Drilling diameter	2 - 13mm
Paper carriage	-
Back margin	5 - 215mm / 0.19" - 8.47" (5 - 390mm / 0.19" - 15.4" with 2W, 4W)
Drilling pattern	Pre-programmed pitch bar
Table size	XA-2, XA-4: 900(W)x610(D)mm/35.5"(W)x24"(D) XA-2W, XA-4W: 1,200(W)x800(D)mm/47.3"(W)x31.5"(D)
Dimensions	XA-2, XA-4: 1,135(W)x1,050(D)x1,360(H)mm/44.7"(W)x41.4"(D)x53.6"(H) XA-2W, XA-4W: 1,295(W)x1,230(D)x1,360(H)mm/51"(W)x48.5"(D)x53.6"(H)
Power source	220 - 240 , 380 , 400 , 450VAC (3 phase), 50 or 60Hz-
Power consumption	1.6kW (XA-2W, 4W: 1.65kW)
Net weight	370kgs/816lbs (XA-2W, 4W: 400kgs/882lbs)
Safety standard	-
Options	Inverter to control the drill bit rotation speed, Round corner unit, Universal pitch gauge Spindle head for 9 - 13mm drill bit, Caster base

Specifications are subject to change without notice.

NEOSYS VIETLOI COMPANY LIMITED

Showroom: No.26B, Street 10, Thao Dien Ward, Dist.2, HCMC, Vietnam
 HN Branch: 3rd Floor, No.6, Lane 2, Quan Ngua St., Ba Dinh Dist., Hanoi, Vietnam
 Tel: (+8428) 22532772/ 25532773 - Fax: (+8428) 22532771
 Website: www.neosys-vietloi.com.vn
 Email: info@neosys-vietloi.com.vn
Hotline: 0902 886 117