



EBA 2331

EBA 5131

EBA 5141

| Model | 2331 S | 2331 C | 2331 C | 2331 CCC | 5131 C | 5131 C | 5131 CCC | 5141 S | 5141 C | 5141 C | 5141 CC | 5141 CCC |
|--|-----------------|-----------|-----------|----------|------------------|-----------|----------|------------------|-----------|-----------|----------|----------|
| Feed opening, mm | 310 | 310 | 310 | 310 | 310 | 310 | 310 | 405 | 405 | 405 | 405 | 405 |
| Shredder type | strip cut | cross cut | cross cut | fine cut | cross cut | cross cut | fine cut | strip cut | cross cut | cross cut | fine cut | fine cut |
| Shred width, mm | 4 | 4 x 40 | 2 x 15 | 0.8 x 5 | 4 x 40 | 2 x 15 | 0.8 x 5 | 6 | 4 x 40 | 2 x 15 | 0.8 x 12 | 0.8 x 5 |
| Performance in sheets, A4 paper 70 g/m ² | 30-32 | 25-27 | 15-17 | 5-7 | 40-45 | 25-30 | 11-12 | 50-55 | 40-45 | 25-30 | 15-17 | 10-11 |
| Performance in sheets, A4 paper 80 g/m ² | 26-28 | 21-23 | 13-15 | 4-6 | 34-39 | 21-26 | 9-10 | 42-47 | 34-39 | 21-26 | 13-15 | 8-9 |
| Security ISO / IEC 21964 (DIN 66399) | P-2 | P-4 | P-5 | P-7 | P-4 | P-5 | P-7 | P-2 | P-4 | P-5 | P-6 | P-7 |
| Shreds also | | | | - | | | - | | | | - | - |
| Paper clip proof solid steel cutting shafts | • | • | • | - | • | • | - | • | • | • | - | - |
| Cutting shaft warranty for 10 years | • | • | • | - | • | • | - | • | • | • | - | - |
| Automatic oiler | - | optional | optional | optional | standard | | | standard | | | | |
| Shred speed, m/sec. | 0.08 | 0.10 | 0.10 | 0.09 | 0.15 | 0.15 | 0.15 | 0.19 | 0.15 | 0.15 | 0.15 | 0.18 |
| Volume of cabinet in litres | 140 | | | | 180 | | | 210 | | | | |
| Shred bin volume in litres | 120 | | | | 140 | | | 165 | | | | |
| Power connection, volts / Hz (single phase) ¹ | 230 / 50 / 1~ | | | | 230 / 50 / 1~ | | | 230 / 50 / 1~ | | | | |
| Motor capacity, W | 640 | | | | 1600 | | | 1600 | | | | |
| Automatic start/stop via photo cell | • | | | | • | | | • | | | | |
| ECC – Electronic Capacity Control | • | | | | • | | | • | | | | |
| Control element | EASY-SWITCH | | | | EASY-SWITCH | | | EASY-SWITCH | | | | |
| SPS Safety Protection System: | • | | | | • | | | • | | | | |
| – Patented safety flap in the feed opening | electronic | | | | electronic | | | electronic | | | | |
| – Automatic reverse / automatic power cut-off | • | | | | • | | | • | | | | |
| – Automatic cut-off if shred bin is full | • | | | | • | | | • | | | | |
| – Electronic door protection | • | | | | • | | | • | | | | |
| – Double motor protection | • | | | | • | | | • | | | | |
| – Zero energy standby mode | • | | | | • | | | • | | | | |
| Awarded the "Blue Angel" ² | • | | | | • | | | • | | | | |
| High quality wooden cabinet, mobile on castors | • | | | | • | | | • | | | | |
| Dimensions, mm (H x W x D) | 930 x 538 x 470 | | | | 1020 x 548 x 590 | | | 1010 x 640 x 590 | | | | |
| Weight, kg | 52 | | | | 102 | | | 115 | | | | |

NEOSYS VIETLOI COMPANY LIMITED

Showroom: No.26B, Street 10, Thao Dien Ward, Dist.2, HCMC, Vietnam
 HN Branch: 3rd Floor, No.6, Lane 2, Quan Ngua St., Ba Dinh Dist., Hanoi, Vietnam
 Tel: (+8428) 22532772/ 25532773 - Fax: (+8428) 22532771
 Website: www.neosys-vietloi.com.vn
 Email: info@neosys-vietloi.com.vn

Hotline: 0902 886 117

¹ other voltages available

² for high energy efficiency

