



EXCELAM II Series

355Q 655Q



DESKTOP ROLL
LAMINATORS

Features of EXCELAM II series

- Pre-set functions include hot and cold settings, pre-heat, temperature measurement, and reverse with over-ride for full speed and temperature control
- Tension Control on Film Mandrel
- Speed Setting from 0~1.3 meters/minute
- Paper Guide on Feed Table
- MAX 5mm Thickness for FOAMBOARD® Mounting
- Variable Pressure Control



Model Name	EXCELAM II-355Q	EXCELAM II-655Q
Max. Laminatin Speed	1.3m/min	1.3m/min
Max. Laminating Width	355mm	655mm
Laminating Films	25mic~500mic	25mic~500mic
Substrate Thickness	80g/m ² ~350g/m ²	80g/m ² ~350g/m ²
Thickness Mount	5mm	5mm
Front Roller Diameter	55mm	55mm
Rear Roller Diameter	30mm	30mm
Power Requirements	220~240V, 50/60Hz	220~240V, 50/60Hz
Power Consumption	1400W, 6.0A	1700W, 7.0A
Warm Up Time	10 minutes	10 minutes
Heating System	Hot Roller Internal Infrared heater	Hot Roller Internal Infrared heater
Operating Temperature	150°C Max.	150°C Max.
Speed Control	Key Pad	Key Pad
Temperature Control	Key Pad	Key Pad
Pressure Adjustment	Manual(6step)	Manual(6step)
Film Core	14~25WH	14~25WH
Cooling System	AC Fan	Blower
Dimensions(WxLxH)	585 x 450 x 285mm	885 x 450 x 285mm
Type of Main Motor	DC W-Geard Motor /36V70	DC W-Geard Motor /36V70
Stand	N/A	Option

※ GMP reserves the right to change specifications without prior notice.

EXCELAM II Series